

LANmark Industry IP65/67 outlets

LANmark Industry IP65/67 outlet kit 2 Snap-In Category 7A black

Nexans Ref.: N42i.003

- Industrial outlet with 2 connectors LANmark-7A GG45 shielded
- IP65/67 Protection level (Dust/Liquids)
- Easy termination, without punch down tool.
- Full conformity with the physical and mechanical requirements of the ISO/IEC 24702
- Conform with IEC61073-3-106 (8way Industrial connector)
- 2 connectors LANmark-7A GG45 shielded included

DESCRIPTION

Application

The LANmark Industry IP65/67 outlet is designed to enable the installation of LANmark-7A Snap-in connectors in industrial and harsh areas. It is conceived for wall mount installation with cable penetration from below or above. The IP65/67 outlet can be used in structured industrial cabling and as interface with the production islands.

Performance

The LANmark-7A Snap-in connector has been designed to reach the highest performance in Category 7A and Class FA. It has outstanding performance for attenuation (insertion loss), NEXT/FEXT, Power Sum NEXT/FEXT and Return Loss exceeding the Cat 7A connector specs as in ISO/IEC 11801:2011. Used with Nexans LANmark Industry cables and patchcords, the connector is independantly tested to exceed the link and stringent four-connector channel requirements as defined in the ISO/IEC11801:2011. As such it supports all data applications defined for Cat 5e, Cat 6, Cat 6A and Cat 7A, such as:

- 10baseT
- Fast Ethernet
- Gigabit Ethernet
- 10G-Base-T
- 155 ATM
- 622 ATM,
- 1.2 ATM
- Industrial Ethernet

Guarantees

The LANmark-7A Snap-in connector is covered by the guarantee as in The General Terms and Conditions of Sales.



LANmark
Industry

STANDARDS

International ISO/IEC 11801;
ISO/IEC 24702



Mechanical resistance to impacts
Normal industrial use



Electro magnetic interference resistance
Yes



Minimum operating temperature
-40 °C



Maximum operating temperature
70 °C



Water proof
IP 65/67



Weather resistance
Excellent

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 5/20/22 www.nexans.dk Page 1 / 3

Nexans

LANmark Industry IP65/67 outlets

LANmark Industry IP65/67 outlet kit 2 Snap-In Category 7A black

Installation

The LANmark-7A Snap-in connectors are designed for an easy and rapid termination. Fitting them inside the IP65/67 outlet is a straight forward operation.

- Fast termination of cable
- Colour code : TSB568A & TSB568B
- Can be used with all types of cables : F²TP, UTP, SF/UTP or STP
- Accepts 24, 23 and 22 AWG cable, PUR, LSZH
- For all LANmark Industry cables



Mechanical resistance to impacts
Normal industrial use



Electro magnetic interference resistance
Yes



Minimum operating temperature
-40 °C



Maximum operating temperature
70 °C



Water proof
IP 65/67



Weather resistance
Excellent

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 5/20/22 www.nexans.dk Page 2 / 3

LANmark Industry IP65/67 outlets

LANmark Industry IP65/67 outlet kit 2 Snap-In Category 7A black

CHARACTERISTICS

Construction characteristics

Connector type	RJ 45
Screen	Yes
Cable entry	From the top or the bottom
Colour	Black
Material	Polycarbonate

Dimensional characteristics

Length cable end on inner side	230 mm
Number of cables	2
Height	173 mm
Width	90 mm
Depth	69 mm
Wall thickness	2.5 mm
Approximate weight per piece	0.29 kg
Dimensions of screw	4.00mm
Number of screws	4

Electrical characteristics

Maximal operating frequency	1000 MHz
Characteristic impedance	100 Ohm

Mechanical characteristics

Mechanical resistance to impacts	Normal industrial use
----------------------------------	-----------------------

Usage characteristics

Component function	Cabling and Connectivity solutions
Field of application	Industrial installations
Number of ports	2
Category	Cat. 7A
Electro magnetic interference resistance	Yes
Packaging	Box
Minimum operating temperature	-40 °C
Maximum operating temperature	70 °C
Water proof	IP 65/67
Weather resistance	Excellent

SELLING AND DELIVERY INFORMATION

Includes automatic shutters, 2xCable Glands, 2xLANmark-7A shielded connector, 1xLabelling window. Colour: Black RAL9011